

Heat Transfer Vinyl Buy with Confidence.

Cut in reverse,place vinyl in machine with clear <u>carrier down</u> Always test cut because of your blade condition

EasyWeed® <u>SETTINGS</u>

Silhouette Cameo: Blade: Standard, 3 Setting: Heat Transfer Material (smooth) Speed: 8 Thickness: 6

Cricut®: Blade: Standard Setting: Iron-on Roland GS/GX-24: Blade: 45° Gram Force: 80-90 Offset: .250 Speed: 25-50 cm/s

Scan N Cut: Blade: 2 Cut Speed: 1

Cut Pressure: 1

Graphtec: Blade: 45° Gram Force: 8-9 Tool: CB09U+0 Speed: 30 cm/s

Glitter <u>SETTINGS</u>

Silhouette Cameo: Blade: Standard, 4 Material: Heat Transfer ,smooth Speed: 8 Thickness: 11

Cricut®: Blade: Standard Setting: Iron On+

Roland GS/GX-24: Blade: 45° Gram Force: 180-190 Offset: .250 Speed: 30 cm/s

Scan N Cut: Blade: 3 Cut Speed: 1 Cut Pressure: 5

Graphtec: Blade: 45° Gram Force: 17 Tool: CB09U+0 Speed: 30 cm/s

Application instructions

(Home iron)

- Set iron dial between Cotton and Linen
- Cover design with Kraft paper.
- Place on flat, hard surface (ironing board not recommended)
- Press iron with VERY Firm Pressure(do not slide iron)
- Press each section for 10-15 seconds
- Peel carrier hot, cover and reheat **again** for 2-3 seconds.

(Heat press)

- Preheat garment for 2-3 seconds
- Apply design at **EasyWeed:**305°F/150°C, **Glitter:** 320°F/160°C
- Use medium pressure for 10-15 seconds
- Peel carrier hot, cover and reheat again for 2-3 seconds.